

MONOFLEX

Food-grade - Standard duty flexible hose for suction and delivery of liquids

Tuyau flexible alimentaire pour le pompage et le refoulement de liquide pour un usage standard










Structure : Flexible hose made out of soft food-grade PVC wall in accordance with the modified EU regulation 10/2011, reinforced with shock resistant PVC spiral.

Applications : Designed for standard duty suction and delivery of liquids compatible with PVC in agriculture, industrial, irrigation and water supply applications.



Structure : Tuyau flexible fait d'une paroi PVC souple de qualité alimentaire selon la norme 10/2011 modifiée, renforcé d'une spirale en PVC rigide de qualité antichoc.

Applications : Conçu pour une utilisation standard d'aspiration et de refoulement de liquides compatibles avec le PVC dans l'agriculture, l'industrie, l'irrigation, les applications d'approvisionnement en eau.

|  |  |  |  |  |  |  |
|---|---|---|---|---|---|--|
| int mm | ext mm | kg/m | mm | bar | bar | m |
| 16 | 22,3 | 0,190 | 64 | 8 | 0,80 | 25/50 |
| 20 | 26,3 | 0,245 | 80 | 8 | 0,80 | 25/50 |
| 25 | 31,4 | 0,310 | 100 | 7 | 0,80 | 25/50 |
| 30 | 36,6 | 0,400 | 120 | 6 | 0,80 | 25/50 |
| 32 | 38,8 | 0,430 | 128 | 6 | 0,80 | 25/50 |
| 35 | 42,1 | 0,470 | 140 | 6 | 0,80 | 25/50 |
| 38 | 45,7 | 0,530 | 152 | 6 | 0,80 | 25/50 |
| 40 | 47,8 | 0,560 | 160 | 6 | 0,80 | 25/50 |
| 45 | 53,3 | 0,670 | 180 | 5 | 0,80 | 25 |
| 51 | 59,7 | 0,800 | 200 | 5 | 0,80 | 25/50 |
| 55 | 63,9 | 0,880 | 220 | 5 | 0,76 | 25 |
| 60 | 69,2 | 0,980 | 240 | 5 | 0,76 | 25 |
| 63 | 72,5 | 1,050 | 252 | 5 | 0,76 | 25 |
| 70 | 80,1 | 1,150 | 280 | 4 | 0,76 | 25 |
| 76 | 86,3 | 1,385 | 300 | 4 | 0,76 | 25 |
| 80 | 91,3 | 1,560 | 320 | 4 | 0,76 | 25 |
| 90 | 101,9 | 1,800 | 360 | 4 | 0,76 | 25 |
| 102 | 115 | 2,160 | 400 | 3 | 0,70 | 25 |
| 105 | 118,2 | 2,160 | 420 | 3 | 0,65 | 25 |
| 110 | 123,0 | 2,400 | 440 | 3 | 0,65 | 25 |
| 120 | 133,6 | 2,800 | 480 | 3 | 0,60 | 25 |
| 152 | 166,0 | 4,250 | 600 | 3 | 0,60 | 25 |
| 160 | 175,9 | 4,400 | 640 | 3 | 0,60 | 10 |
| 203 | 223,0 | 6,400 | 950 | 2 | 0,60 | 10 |



Printing | Marquage :

MONOFLEX  CE 10/2011 n°lot

Temperature | Température :

-5 / + 60 °C
23 / + 140 °F

Properties | Caractéristiques :

Smooth inside, corrugated outside.
Lisse intérieur, ondulé extérieur.

Colors | Couleurs :

